

Technical data sheet

PROTECT 371

Alkyd primer fast-drying

Modified fast-drying primer based on alkyd resin.

USE:

- Means of transport
- Machines and equipment

PROPERTIES

- High yield
- Good hiding power and flowability
 - Good filling properties
 - Good chemical resistance
- Application of thick layers is possible
 - Good mechanical resistance
- Possibility of the application up to 250 µm wet in a single layer

PROTECT 371

Technical data sheet
2026/06/03

2020/05/05

DRYING TIME				
	For the max. dry coating thickness of 80 µm.	Dust-free	10°C	20°C
			1.5 hours	45 min.
		Tack-free	2 hours	1 hours
		Operating hardness	6 hours	2.5 hours
COATABILITY				
Topcoat application time for a 80 µm thick primer.		10°C	20°C	
		3 hours	45 min.	
Coatable by all NOVOL alkyd topcoats. The time to recoat ranges from 1 hour to 7 days before sanding, assuming the coat is free of salts, grease, dust, and foreign debris. It is recommended to degrease and sand the coat after 7 days.				
TECHNICAL DATA				
Product	Solids content by weight	Solids content by volume	Density	Fineness of grind
PROTECT 371	≈ 72 %	≈ 60 %	≈ 1.3 ÷ 1.5 g/cm³	< 25µm
CONTENT OF VOLATILE ORGANIC COMPOUNDS				
VOC II/B/c limit*		540 g/l		
Actual VOC content		375 g/l		
* For the ready to apply mixture compliant with Directive UE 2004/42/CE				
APPLICATION CONDITIONS				
The coated surface should be dry. The temperature of the coat, coated surface and environment should be between +10°C and +35°C at a maximum relative humidity of 80%. The coated surface temperature should exceed the dew point by a minimum of 3°C.				
TEMPERATURE RESISTANCE				
The operating temperature of the applied primer is between -60°C and +80°C. Transient temperatures up to +120°C maximum are permitted.				
COLOUR				
Grey, dark grey, black, red, white.				
EQUIPMENT CLEANING				
THIN 50.				
STORAGE CONDITIONS				
Store in a dry room, away from sources of flame and heat. Avoid direct exposure to sunlight. Recommended storage temperature: +5°C to +35°C.				

PROTECT 371

Technical data sheet
2026/06/03

SHELF LIFE	
PROTECT 371	12 months/20 °C
SAFETY	
See Safety Data Sheet.	
OTHER INFORMATIONS	
Registration number: 000024104. The effectiveness of our systems results from laboratory research and many years of experience. The data contained herein meets the current knowledge about our products and their application potential. We ensure high quality, provided the user follows the instructions and the work is performed in accordance with good workmanship. It is necessary to do a test application of the product due to its potentially different reaction with different materials. We may not be held liable for defects if the final result was affected by factors beyond our control.	